Cypress Soaring PW-5 Pre-Flight Checklist

Remove gust locks & tiedowns												
Inspect forward fuselage												
Pitot & Static ports clear												
Check weight limits												
INSTALL BATTERY- (reqd equipment)												
Seat Back secured												
Airworthiness, Registration Certif.												
Altimeter set												
Airspeed indicator- check												
Belts- check condition, latches												
Tow Relase-- Condition												
CONTROLS-- Free & Operative												
Trim set- Position 5=Heavy, Position 2=Light												
Wing Bolts- Latched												
Spoilers-Check Operation												
Wheel Brake operative												
Canopy locks operative-												
Canopy Emergency Jettison pin: Installed												
Bilge Clean												
Landing Gear (Nose =29 psi; Main =36 psi)												
Left Wing Conformity												
Left Aileron-deflection, play, friction												
Left Wing Spoilers												
Aileron & Spoiler linkages-Locked												
Fuselage access cover secure												
Left fuselage & bottom conformity												
Vertical stabilizer surfaces												
Total Energy Probe – installed & secure												
Rudder Hinges & cables- free and operative.												
Horizontal Stabilizer Pin - locked												
Elevator-check deflection, play, friction												
Tailwheel- operational												
Right fuselage conformity												
Right wing spoilers												
Right wing conformity												
Right aileron- deflection, play, friction												
Retract spoilers and lock												
Radio & Battery operative												
Adjust rudder pedals												
POSITIVE CONTROL CHECK												
Parachute required!												
WASH AIRCRAFT												
	Date											
PW-5 Pre-Flight Checklist	Name											