Cypress Soaring PW-6U	Pre-	-Fli	ght	Ch	ec	:kli	ist	Revi	sed	02/10	)/201	9			
Remove gust locks & tiedowns												-		_	
Inspect forward fuselage								+							
Inspect static ports															
Check front/rear seat weight limits								+							
Install battery and secure-(reqd eqpt)								-							
Secure rear seat back	+							+							
Airworthiness, registration certif.								+				_		 _	
Altimeter set, front/rear								-				_	 	 _	
Airspeed indicator- check								-				-			
Seat belts- check condition, latches	$\vdash$			-				-							
Tow hook condition	$\left  \right $			-				-					 		
Controls free & operative	$\vdash$	_		-				+						 	
	$\vdash$							+					 	 	
Trim set– position 5=Heavy, 2=Light	$\vdash$							_	<u> </u>				 		
Wing bolts- latched Airbrakes– check Operation	$\vdash$			-				-							
	$ \longrightarrow $							-					 	 	
Wheel brake operative	┝──┤	-+	_				$\vdash$	+							
Canopy latches operative. Canopy hinges															
secure, front & rear. Emergency Jettison															
pin: Remove for flights w/o parachutes.															
Install for flights w/ parachutes.	$\vdash$	-+		-			$\vdash$	+							
Bilge clean, cockpit free loose items	┝──┤	-+					$\vdash$	+							
Tire pressure Main= 45psi, nose=22psi	$\vdash$						$\vdash$	_							
Left wing conformity	$\vdash$						$\vdash$	_							
Left aileron– deflection, play, friction	$ \longrightarrow $		_					_							
Left wing airbrakes								_							
Aileron & airbrake linkages– locked								_							
Fuselage access cover secure															
Left fuselage & bottom conformity								_							
Vertical stabilizer surfaces	$\square$							_							
Total energy probe- secure								_							
Rudder hinges & cables															
Horizontal stabilizer pin- locked															
Elevator- check deflection, play, friction															
Elevator attachments															
Tailwheel - 29psi															
Right fuselage conformity															
Right wing spoilers															
Right wing conformity															
Right aileron- deflection, play, friction															
Retract airbrakes and lock															
IF SOLO FLIGHT: Secure rear seat belts,															
LOCK rear canopy															
Radio & Battery operative								1							
Adjust Front cockpit rudder pedals		-+						+							
Positive control check	<u>├</u>						$\vdash$	-							
Wash aircraft	├──┤						$\vdash$	+							
Solo Flight Note:	╞──┤							+	-						
(1) Check rear seat back is secure. (2) Verify															
O2 tank does not interfere w/controls. (3)															
Have ground crew verify rear canopy latched.															
Data														 	
Date															
Name															
DW-611 Proflight Chacklist															
PW-6U Preflight Checklist															